

ELECTROTHERAPY EQUIPMENTS

LCS 131



LCS 132



LCS 133



CERVICAL cum LUMBER TRACTION

LCS CERVICAL cum LUMBAR TRACTION is a modern electro mechanical system; molded aluminum gearbox & metal gears give long life & jerk free traction. It is based on solid-state circuitry; it has silent, smooth & powerful motor to pull the appropriate weight, separate traction force selection for CERVICAL & LUMBER.

APPLICATION

For the treatment of Lumbar, Cervical and Upper Dorsal Region.

LCS 133DX



SPECIFICATION	LCS 131	LCS 132	LCS 133	LCS 133 DX
Dimension (L*H*D)	326mm, 280mm, 307mm	326mm, 280mm, 325mm	326mm, 280mm, 325mm	326mm, 280mm, 325mm
Weight	11 kg.(Approx.)	12 Kg. (Approx)	11.5 Kg. (Approx)	12 Kg. (Approx)
Operating Voltage	220V AC, 50hz	220V AC, 50Hz	220V AC, 50Hz	220V AC, 50Hz
Absorption	37-Watts Max	37-Watts Max	37-Watts Max	37-Watts Max
Fuses	500 mA	500 mA	500 mA	500 mA
Room Temperature	10°C to 40°C.	10°C to 40°C.	10°C to 40°C.	10°C to 40°C.
Moisture	10% to 80%	10% to 80%	10% to 80%	10% to 80%
Treatment Mode	Static/Intermittent (LED Display)	Static/Intermittent	Static/Intermittent	Static/Intermittent
Traction Force	5 to 45 kg (with doubler 90 kg)	4 to 45 Kg (with doubler 90 Kg)	4 to 45 Kg (with doubler 90 Kg)	4 to 45 Kg (with doubler 90 Kg)
Cervical	-	4 to 15 Kg (each 1 Kg steps)	4 to 15 Kg (each 1 Kg steps)	4 to 14 Kg (each 1 Kg steps)
Lumber	-	23 to 45 Kg (each 2 Kg steps)	23 to 45 Kg (each 2 Kg steps)	25 to 45 Kg (each 2 Kg steps)
Hold Time	10, 20, 40, 60, 80 Sec. with LED Display	10, 20, 40, 60, 80 Sec. with LED Indicator	01~99 Sec. with Digital Display	01~99 Sec. with Digital Display
Rest Time	1, 5, 10, 15, 20 Sec. with LED Display	1, 5, 10, 15, 20 Sec. with LED Indicator	01~99 Sec. with Digital Display	01~99 Sec. with Digital Display
Treatment Time	01-99 minutes presentable (Set between 01-99 min. Optional)	01 ~ 99 minutes	01 ~ 99 minutes	01 ~ 99 minutes
Patient Safety	Available	Available	Available	Available